




VALVULA DE RETENCION TIPO CLAPETA SERIE 1500 – PN 260

CLASS 1500 SWING CHECK VALVE – PN 260

Válvula de RETENCION TIPO CLAPETA, acero carbono, fundido, ASTM A216 Gr.WCB, extremos bridados. Bonete abulonado, Asiento renovable. Montaje API 600 Trim 1.

SWING CHECK valve, cast carbon steel, ASTM A216 Gr.WCB, flanged ends. Bolted bonnet, Renewable seat ring. Trim API 600 1.



It.	Descripción	Material estándar	It.	Description
01	Cuerpo	ASTMA A 216 Gr.WCB	01	Body
04	Asiento	ASTMA A 216 Gr.WCB + 13%Cr.	04	Seat ring
12	Palanca	ASTMA A 216 Gr.WCB	12	Hinge or disc carrier
21	Junta	Graphite / Stainless steel	21	Gasket
23	Espárrago cuerpo-bonete	ASTMA A 193 Gr.B7	23	Body-bonnet stub
33	Tuerca cuerpo-bonete	ASTMA A 194 Gr.2H	33	Body-bonnet nut
72	Bonete	ASTMA A 216 Gr.WCB	72	Bonnet
75	Disco	ASTMA A 216 Gr.WCB + 13%Cr.	75	Disc
76	Tuerca bloqueo disco	ASTMA A 276 Gr.316	76	Disc lock-nut
77	Espina de bloqueo	ASTMA A 276 Gr.316	77	Pin
78	Eje	ASTMA A 276 Gr.410	78	Axis
79	Tapón bloqueo eje	ASTMA A 105	79	Bumper plug

SERIE 1500 - PN 260

CLASS 1500 - PN 260

Medida Nominal Nominal Size		RF ASME B16.10 A	BW ASME B16.10 A ₁	Altura Height B	Diámetro ASME B16.5 D	Peso Weight RF kg.
Inch	DN (mm)					
2"	50	368,3	368,0	250,0	215,9	86,0
2 ½"	65	419,1	419,1	280,0	244,3	116,0
3"	80	469,9	469,9	295,0	266,7	124,0
4"	100	546,1	546,1	385,0	311,1	231,0
6"	150	704,8	704,8	500,0	393,7	585,0
8"	200	831,8	831,8	510,0	482,6	945,0
10"	250	990,6	990,6	560,0	584,2	1275,0
12"	300	1130,3	1130,0	650,0	673,1	1870,0
14"	350	1257,3	1257,3	750,0	749,3	2560,0
16"	400	1384,3	1384,3	800,0	825,5	3260,0

